

| | Seat Height | Arm Height | W | D | H | Fabric | Leather | Weight | Cubes/Qty |
|---------------|-------------|------------|--------|--------|---------|----------|---------|---------|------------|
| avenue | 18-20¾" | 25½-27¾" | 24½" | 27" | 35¼-38" | 2.0 yds. | 34.0' | 90 lbs. | 28.99' / 1 |
| | 527 mm | 708 mm | 622 mm | 686 mm | 965 mm | 1.8 m | 3.2 sqm | 40.8 kg | .82 cu. |



GREENGUARD Certified

517 - Black Cast Aluminum Base

| COM | COL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 1266 | 1306 | 1418 | 1435 | 1453 | 1471 | 1484 | 1498 | 1511 | 1529 | 1569 | 1615 | 1695 |

518 - Polished Cast Aluminum Base

| COM | COL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 1319 | 1359 | 1471 | 1488 | 1506 | 1524 | 1537 | 1551 | 1564 | 1582 | 1622 | 1668 | 1748 |

Mid Back. Loop Arms. *All COM/COL fabrics must be preapproved by Bernhardt Design prior to application. Approved for GSA.

Base: Swivel/tilt mechanism with 2 degrees forward pitch and standard gas pneumatic lift cylinder. Unit sits on a 26" 5-star cast aluminum base with black dual wheel casters.

Seat and Back: Upholstered molded polyurethane foam mounted to mid-back molded plywood shell.

Arms: Laser cut steel with black self-skinning polyurethane foam covering.

avenue

| | | | | | | | | |
|---------|----------|--------|--------|---------|----------|---------|---------|------------|
| 18-20¾" | 25½-27¾" | 24½" | 27" | 35¼-38" | 2.5 yds. | 51.0' | 95 lbs. | 28.99' / 1 |
| 527 mm | 708 mm | 622 mm | 686 mm | 965 mm | 2.3 m | 4.7 sqm | 43.1 kg | .82 cu. |



GREENGUARD Certified

519 - Black Cast Aluminum Base

| COM | COL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 1488 | 1538 | 1677 | 1700 | 1722 | 1744 | 1761 | 1777 | 1794 | 1816 | 1866 | 1925 | 2025 |

520 - Polished Cast Aluminum Base

| COM | COL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 1541 | 1591 | 1730 | 1753 | 1775 | 1797 | 1814 | 1830 | 1847 | 1869 | 1919 | 1978 | 2078 |

Mid Back. Upholstered Arms. *All COM/COL fabrics must be preapproved by Bernhardt Design prior to application. Approved for GSA.

Base: Swivel/tilt mechanism with 2 degrees forward pitch and standard gas pneumatic lift cylinder. Unit sits on a 26" 5-star cast aluminum base with black dual wheel casters.

Seat and Back: Upholstered molded polyurethane foam mounted to mid-back molded plywood shell.

Arms: Upholstered rigid molded foam.

| | Seat Height | Arm Height | W | D | H | Fabric | Leather | Weight | Cubes/Qty |
|---------------|-------------|------------|--------|--------|---------|----------|---------|----------|-----------|
| avenue | 18-20¾" | 25½-27¾" | 26½" | 27" | 38-40¾" | 2.1 yds. | 39.1' | 100 lbs. | 28.99'/1 |
| | 527mm | 708 mm | 673 mm | 686 mm | 1035 mm | 1.9 m | 3.6 sqm | 45.3 kg | .82 cu. |



523 - Black Cast Aluminum Base

| COM | COL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 1386 | 1428 | 1545 | 1564 | 1582 | 1601 | 1615 | 1629 | 1643 | 1662 | 1704 | 1753 | 1837 |

524 - Polished Cast Aluminum Base

| COM | COL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 1432 | 1474 | 1591 | 1610 | 1628 | 1647 | 1661 | 1675 | 1689 | 1708 | 1750 | 1799 | 1883 |

High Back. Loop Arms. *All COM/COL fabrics must be preapproved by Bernhardt Design prior to application. Approved for GSA.

Base: Swivel/tilt mechanism with 2 degrees forward pitch and standard gas pneumatic lift cylinder. Unit sits on a 26" 5-star cast aluminum base with black dual wheel casters.

Seat and Back: Upholstered molded polyurethane foam mounted to high back molded plywood shell.

Arms: Laser cut steel with black self-skinning polyurethane foam covering.

| | Seat Height | Arm Height | W | D | H | Fabric | Leather | Weight | Cubes/Qty |
|---------------|-------------|------------|--------|--------|---------|----------|---------|----------|-----------|
| avenue | 18-20¾" | 25½-27¾" | 26½" | 27" | 38-40¾" | 2.6 yds. | 52.7' | 100 lbs. | 28.99'/1 |
| | 527 mm | 708 mm | 673 mm | 686 mm | 1035 mm | 2.4 m | 4.9 sqm | 45.3 kg | .82 cu. |



525 - Black Cast Aluminum Base

| COM | COL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 1534 | 1586 | 1731 | 1754 | 1777 | 1800 | 1818 | 1835 | 1852 | 1875 | 1927 | 1988 | 2092 |

526 - Polished Cast Aluminum Base

| COM | COL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 1581 | 1633 | 1778 | 1801 | 1824 | 1847 | 1865 | 1882 | 1899 | 1922 | 1974 | 2035 | 2139 |

High Back. Upholstered Arms. *All COM/COL fabrics must be preapproved by Bernhardt Design prior to application. Approved for GSA.

Base: Swivel/tilt mechanism with 2 degrees forward pitch and standard gas pneumatic lift cylinder. Unit sits on a 26" 5-star cast aluminum base with black dual wheel casters.

Seat and Back: Upholstered molded polyurethane foam mounted to high back molded plywood shell.

Arms: Upholstered rigid molded foam.